

Steel post shore EP

Take advantage of our **galvanized steel post shore** designed for shoring and reshoring of slab formwork



Call or text us today for more details at 770-910-7510 or email us to sales@ulmaconstruction.us

When you buy from **ULMA**, you are buying **quality** products for years to come with **exceptional service** from a global industry leader.

FROM \$45
EACH POST SHORE

USED EQUIPMENT IN GOOD CONDITION

I FEATURES

	EP POST SHORE	USAGE LENGTH (min max.)	STATIC COMPRESSION (max min.)
\$ 45	EP C+D30	5′11″ - 9′10″	8.5 kips - 7.5 kips
\$ 57	EP C+D35	6′7″ - 11′6″	8.5 kips
\$ 99	EP C+D40	7′7″ - 13′1″	8.5 kips - 7.5 kips
\$ 55	EP C+E40	7′7″ - 13′1″	7.5 kips

Closed Prop Length = Min. Usage Lentgh - 0.78 inches / 20 mm approx.


I FAST DELIVERY



BENEFITS

· Guaranteed high safety levels:

- Designed in accordance to the standard EN 1065. Certification marking is incorporated in the handle (*).
- · Simple and quick adjustment of the collar nut.
- · Inner tube, clevis pin and collar nut with unintentional disengagement system.
- · Cost-effective due to an optimized design.



· Ideal for repropping.

- System for fast post shore stripping included in the clevis pin.
- Collar nut with projection for simplified adjustment of the post shore.
- High durability for multiple reuse, thanks to the hot-dip galvanization that provides excellent protection against corrosion.
- Simple and quick maintenance. The collar nut has a thread designed to remove dirt and concrete remains.
- Compatible with various ULMA shoring systems: ENKOFLEX, CC-4, VR TABLES, FORMADECK ...





EP post shore with CC-4